

UNIVERSAL ISS 165

2 way component kit



• Butyl surround
Perfect reliability

• Phase plug
Better dispersion

• Polyglass cone
Neutral sound without coloration

• Integrated crossover
(woofer + tweeter)
Easy installation

• Processed aluminum inverted dome tweeter
Smoothness and definition without directivity
• Partial horn loading
Best positioning in the soundstage

ADVANTAGES

- High sensitivity
- Shallow mounting depth (49.9 mm)
- Partial horn loading tweeter
- Dynamics and neutrality
- 2 tweeter support types
- Tweeter compact size



Removable tweeter



Tilted mounting
Easy installation



Assembly option :
car and display

TECHNICAL CHARACTERISTICS

Woofer: 7¹/₂" (165mm)
Voice-coil diameter: 1" (25mm)
Voice-coil height: 0¹/₄" (7mm)
Magnet: 3⁹/₁₆" (90mm)

Processed Aluminum inverted dome tweeter
Integrated crossover: 6dB/oct (woofer + tweeter)
Max. power: 140W
Nom. power: 70W rms

Sensitivity (2,83 V/1 m) : 92.6dB
Frequency response: 60Hz – 20kHz
Accessories: Supplied without grille

 **Integration**
INSTANT GRATIFICATION

 **FOCAL**
THE SPIRIT OF SOUND