

# UNIVERSAL ISS 690

## 2 way component kit



• Butyl surround  
**Perfect reliability**

• Polyglass cone  
**Neutral sound without coloration**

• Integrated crossover  
(woofer + tweeter)  
**Easy installation**

• Processed aluminum inverted dome tweeter  
**Smoothness and definition without directivity**  
• Partial horn loading  
**Best positioning in the soundstage**

## ADVANTAGES

- High sensitivity
- Shallow mounting depth (82.5mm)
- Partial horn loading tweeter
- Dynamics and neutrality
- 2 tweeter support types
- Tweeter compact size
- Toyota® car compatibility



Removable tweeter



Tilted mounting  
Easy installation



Assembly option :  
car and display

## TECHNICAL CHARACTERISTICS

**Woofer:** 6x9" (150x230mm)  
**Voice-coil diameter:** 1<sup>3/16"</sup> (30mm)  
**Voice-coil height:** 0<sup>7/16"</sup> (10.5mm)  
**Magnet:** 3<sup>9/16"</sup> (90mm)

**Processed Aluminum inverted dome tweeter**  
**Integrated crossover:** 6dB/oct (woofer + tweeter)  
**Max. power:** 160W  
**Nom. power:** 80W rms

**Sensitivity (2,83 V/1 m) :** 93.6dB  
**Frequency response:** 55Hz – 20kHz  
**Accessories:** Supplied without grille

 **Integration**  
INSTANT GRATIFICATION

 **FOCAL**®  
THE SPIRIT OF SOUND