

FPP 4100



Quality 4 channel amplifier



• Small size
Easy integration in a vehicle

• Aluminum chassis
High thermal dissipation

• High-pass and low-pass crossover
Numerous settings available

• Remote control
Keep the control

- 1 inch² (25mm²) power supply terminal
No power loss
- High and low-level inputs
Suits any installation
- "Auto Power On" on the high-level input
Easy wiring
- Fader
Benefit from the 4 channels while using only 2 inputs
- Balanced inputs
Floating ground, no parasite



ADVANTAGES

- 3 channel use with bass adjustment
- High-level input, fits the original system
- Secure and easily accessible settings
- Aluminum chassis
- Remote control

TECHNICAL CHARACTERISTICS

Power into 4 Ohms: 4x90W rms
Power into 2 Ohms: 4x140W rms
Bridged mode into 4 Ohms: 2x240W rms
Frequency response: 10Hz–60kHz
Signal/noise ratio: >80dB (A)

Adjustable gain
Dimensions (HxLxD): 2^{3/8}x14^{3/4}x7^{11/16}"
(60x375x195mm)
Protections: Short-circuit, continuous current,
thermal overload

RMS power - 14.4 V- 4 Ohms
THD+N < 1%
(CEA 2006)

4x75W rms

