

K2 POWER ES 165KX2

2-way component kit



Aluminum chassis new design

- Rigid, antimagnetic with exclusive design for a better excursion

K2 Power sandwich cone

- Dynamic & precise

Bi-Amp audiophile crossover

- (Tweeter 0 / +3 / - 3 dB/oct), multi settings
- Reliability and power



Aluminum tweeter housing

- Flush "high tech" fitting design

Integrated terminal

- More compact

Exclusive VC venting system

- High SPL and high power handling

Butyl surround exclusive patent "TMD" (Tuned Mass Damper) with S/N engraved

- Better control, more neutral and linear sound

TKMX "M" profile aramid fiber inverted dome tweeter

- High extension in treble
- Smooth and precision

WHAT MAKES THE DIFFERENCE

- Inverted dome "M"-shaped tweeter
- 1⁹/₁₆" (40mm) VC diameter
- High power handling
- Bi-Amp crossover
- Phase plug for better dispersion
- Aluminum and mesh grille

TECHNICAL CHARACTERISTICS

2-way component kit

Diameter: 6¹/₂" (165mm)

Voice coil diameter: 1⁹/₁₆" (40mm)

Voice coil height: 0²/₃₂" (16.5mm)

Motor: Magnet

Tweeter: TKMX ("M" profile aramid fiber inverted dome)

Cone: Composite K2 Power "W" sandwich cone

Surround: Tuned Mass Damper (TMD®)

Separated crossover: 6-12/12-18dB (3kHz)

Tweeter Adjustable level: +3; 0; -3dB/oct

Max. power: 240W

Nom. power: 120W RMS

Sensitivity (2.83V/1m): 92.5dB

Frequency response: 55Hz- 22kHz

Impedance: 2 Ω

Accessories: Supplied grilles



Elite

"HAUTE COUTURE" SOUND



FOCAL
THE SPIRIT OF SOUND