

D CLASS PREMIUM AMPLIFIER FPX 1.1000

DUAL OUTPUT – POWERFULL AND COMPACT

- High performance compact heat dissipation chassis.





- High power and current dynamic reserve.

- Audio Mos-Fets - Optimized efficiency.

KEY POINTS

- D Class Mono amplifier – High power and current dynamic reserve
- Stable under 1 Ohm
- Audio Mos-Fets - Optimized efficiency
- High performance compact heat dissipation chassis
- Included remote



TECHNICAL SPECIFICATIONS



D Class Mono amplifier

CEA power (4 ohms): 1x420 Wrms

Maximum power (2 ohms): 1x700 Wrms

Maximum power (1 ohm): 1x1000 Wrms

Bandwidth: 15 Hz – 250 Hz

Total harmonic distortion: 0.08 %

SNR (1W/A): > 76 dBA

Low-pass filter: 50Hz-250Hz

Subsonic filter: 10Hz-50Hz

Progressive phase adjustment (0-180°)

Bass boost (0/12dB)

Protections: Short circuit / low impedance / reversal of polarity / DC / power drop / heat protection

Dimensions (LxHxW):

11^{11/16} x 5^{13/64} x 2^{33/32}" (297x132x53mm)

Weight: 5.62lbs (2.55kg)

 **Performance**
CREATE YOUR SOUND

 **FOCAL**
THE SPIRIT OF SOUND