

# 100 KRS

## 2-way K2 Power kit

- K2 composite sandwich cone

### Impact and details

- Zamak chassis

### Rigid and non-magnetic

- Aluminum phase plug

### Mid-range precision

- Butyl surround
- Excellent reliability
- Engraved serial number
- Authenticity certificate

- Adjustable tweeter 3 levels per stage of 3dB

### Installation flexibility

- Polypropylene capacitor

### Neutral reproduction of high frequencies

- Multi-wire air core inductor

### Resistant to parasites, maximum dynamics



- TNK inverted dome tweeter
- Smoothness and precision
- Neodymium ring magnet
- Very high linearity and dynamics
- Foam surround
- Extended frequency response

### Technical characteristics:

100mm (4") Woofer

25mm (1") Voice coil

Magnet: Neodymium

TNK inverted dome tweeter

Separate crossover : 12/12dB/oct (3.5kHz)

Adjustable tweeter level: (0,-3,-6dB)

Max. power: 100W

Nom. power: 50W

Sensitivity (2,83V/1m): 90dB

Frequency response: 120Hz – 20kHz

Accessories: grilles supplied

### It makes the difference:

- Treble smoothness
- Dynamic and neutrality
- Precision of sound stage
- Tweeter sound level adjustment
- Can be used as central speaker in 5.0 or 5.1 system

