

165 KR2

2-way K2 Power kit

- K2 composite sandwich cone
Impact and details
- Zamak chassis
Strong, rigid and non-magnetic chassis
- Butyl surround
Excellent reliability

- Engraved serial number
Certificate of authenticity
- Aluminum phase plug
Better directivity of the mid-range
- Heavy ferrite
Magnetic flux increase

- Adjustable tweeter level per stage of 3dB
Installation flexibility
- Polypropylene capacitor
Neutral reproduction of high frequencies
- Multi-wire air core inductor
Resistant to parasites, maximum dynamic



- TNK inverted dome tweeter
Smoothness and precision
- Neodymium ring magnet
Very high linearity and dynamism
- Foam surround
Extended frequency response

Technical characteristics :

165mm (6.5") Woofer
32mm (1.26") Voice coil
90mm (3.54") Magnet
TNK tweeter
Kevlar inverted dome
Separate crossover : 12/12/18dB/oct (4kHz)
Adjustable tweeter level: (0,-3,-6dB)
Max. power: 160W
Nom. power: 80W
Sensitivity (2,8V/1m): 93dB
Frequency response: 70Hz – 20kHz
Accessories: grilles supplied

It makes the difference:

- Treble smoothness
- Dynamic and neutrality
- Precision of sound stage
- Tweeter sound level adjustment
- Excellent linearity of the two speakers
- High sensitivity
- 2 Ohms impedance

