

# 165 KRXS

## 2-way K2 Power kit

- K2 composite sandwich cone

### Impact and details

- Aluminum basket

### Light and non-magnetic

- Butyl surround

### Excellent reliability

- Engraved serial number

### Authenticity certificate

- Neodymium magnet

### Minimal volume

- TN53K inverted dome tweeter

### Smoothness and precision

- Neodymium ring magnet

### Very high linearity and dynamism

- Foam separate surround

### Extended frequency response

- Phase plug

### Low directivity

- Adjustable tweeter level per step of 3dB

### Easy installation

- Polypropylene capacitor

### Natural treble reproduction

- Air core inductor

### Resistant to parasites, maximal dynamics

- Super Tweeter set up

### Increases high-treble



### Technical characteristics:

Woofer: 6 1/2" [165mm]

Voice coil: 1 1/4" [32mm]

Neodymium magnet

TN53K inverted dome tweeter

Separate crossover: Full/12-12/18dB/oct (3.8kHz)

Adjustable tweeter level: [0, -3, -6dB]

Max. power: 120W

Nom. power: 60W

Sensitivity [2.83V/1m]: 94dB

Frequency response: 75Hz – 20kHz

Accessories: grilles, tweeter support

### It makes the difference:

- Very high sensitivity
- Possibility of super tweeter set up
- Mounting depth 2 3/16" [55.5mm]
- Tight punchy bass

