

165 KR

2-way K2 Power kit

- K2 composite sandwich cone
Impact and details
- Zamak chassis
Strong, rigid and non-magnetic chassis
- Butyl surround
Excellent reliability
- Engraved serial number
Certificate of authenticity

- Adjustable tweeter 3 levels per stage of 3dB
Installation flexibility
- Polypropylene capacitor
Neutral reproduction of high frequencies
- Multi-wire air core inductor
Resistant to parasites, maximum dynamic



- TNK inverted dome tweeter
Smoothness and precision
- Neodymium ring magnet
Very high linearity and dynamism
- Foam surround
Extended frequency response

Technical characteristics :

165mm (6.5") Woofer
25mm (1") Voice coil
85mm (3.5") Magnet
TNK inverted dome tweeter
Separate crossover : 12/12dB/oct (3.8kHz)
Adjustable tweeter level: {0,-3,-6dB}
Max. power: 160W
Nom. power: 80W
Sensitivity (2,83V/1m): 91dB
Frequency response: 60Hz – 20kHz
Accessories: grilles supplied

It makes the difference:

- Treble smoothness
- Dynamic and neutrality
- Precision of sound stage
- Tweeter sound level adjustment
- Excellent linearity of the two speakers
- High sensitivity

