

Performance P165V33



3-way kit

- Aluminum basket
- Strong rigid chassis, non-magnetic**
- 1" (25mm) voice coil on Kapton® former
- High power handling**
- 3^{1/3}" (85mm) magnet
- High efficiency for more dynamics**
- Butyl surround
- Promoting long life**
- Polyglass cone
- Neutral sound without coloration**



- Air core inductor with a low serial resistance
- Insensitive to parasite, better sensitivity**
- Polypropylene/aluminum capacitor
- Natural reproduction of high frequencies**

- Shallow mounting midrange (1^{1/2}" / 39.5mm)
- Easy installation on the dashboard or on the A-pillar**

- Aluminum/magnesium inverted dome TNB tweeter
- Smooth and detailed treble, large and precise sound stage**
- Neodymium magnet
- High linearity tweeter**
- Voice coil on aluminum former
- Excellent heat dissipation characteristic**

- Adjustable tweeter level
- Optimization of the tweeter level according to the location**
- 12/12/12dB/oct. crossover
- Optimum coupling of tweeter, midrange and woofer**

ADVANTAGES

- Shallow mounting midrange for an optimized and easy installation
- Highest fidelity reproduction for an absolute realistic sound
- Large and precise sound stage
- Important dynamics

TECHNICAL CHARACTERISTICS

Woofer: 6^{1/2}" (165mm)
Voice coil: 1" (25mm)
Magnet: 3^{1/3}" (85mm)
Midrange: 4" (100mm)
Neodymium magnet
Tweeter TNB: 1^{3/4}" (45mm)

Aluminum/magnesium inverted dome tweeter
3-way crossover: 12/12/12dB/oct. (400Hz – 4kHz)
Adjustable tweeter level: 0, -3, -6 dB/oct
Max power: 160W
Nom. power: 80W rms

Sensitivity (2.83 V/1m): 93dB
Frequency response: 55Hz – 28kHz
Accessories: supplied grilles